

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
26 May 2005 (26.05.2005)

PCT

(10) International Publication Number  
**WO 2005/046411 A1**

(51) International Patent Classification<sup>7</sup>: **A47J 42/04**,  
42/08

(21) International Application Number:  
PCT/ZA2004/000141

(22) International Filing Date:  
11 November 2004 (11.11.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
2003/8880 14 November 2003 (14.11.2003) ZA

(71) Applicants and

(72) Inventors: **DELBRIDGE, David, Stephen** [ZA/ZA]; 67  
Wireless Road, Kommetjie 7976 (ZA). **DELBRIDGE,**  
**Patrick, John** [ZA/ZA]; 11 Caxton Way, Oakridge 7806  
(ZA).

(74) Agent: **JORDAN, Bernice, S.**; Brian Bacon & Associates  
Inc., 2nd Floor, Mariendahl House, Newlands on Main,  
Main Road, 7700 Newlands (ZA).

(81) Designated States (*unless otherwise indicated, for every  
kind of national protection available*): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.


(84) Designated States (*unless otherwise indicated, for every  
kind of regional protection available*): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,  
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,  
FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE,  
SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,  
GW, ML, MR, NE, SN, TD, TG).

**Published:**

— with international search report

[Continued on next page]

(54) Title: A SPICE GRINDER



(57) **Abstract:** A spice grinder (12) comprising a first, static component (10) which includes threading (14) by means of which it can be screwed onto the threaded neck of a container and a second, rotatable component (16) which fits on the component (10). The first component (10) has a tapering bore with teeth (30) projecting inwardly from the surface of the bore. The second component (16) has a cone (44) with teeth (48) on the outside thereof. The teeth (48) are in the tapering bore whereby grinding takes place in the gap between the teeth of the first and second components upon the second component being rotated. The first and second component (10, 16) have interlocking circumferentially extending ribs and grooves (32, 50, 52) which permit the rotatable component (16) to be moved axially and located in its adjusted position thereby to vary the size of the gap between the teeth (30) of the rotatable component and the teeth (48) of the static component.

WO 2005/046411 A1



— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*